

Glove measurements (mm)

	size	A length	B width	C thumb
CLASSIC 599 64 92-10	one size	200	120	80
FUNCTIONAL Light Vent 529 88 01-XX	7	220	98	61
	8	230	104	64
	9	240	110	67
	10	250	116	70
FUNCTIONAL Light Comfort 599 64 94-XX	6	210	92	58
	7	220	98	61
	8	230	104	64
	9	240	110	67
	10	250	116	70
FUNCTIONAL Light Non Slip 529 88 02-XX	12	265	128	76
	7	220	98	61
	8	230	104	64
	9	240	110	67
FUNCTIONAL Light Non Slip 529 88 02-XX	10	250	116	70
	8	260	109	60
	9	270	113	60
	10	280	117	63
FUNCTIONAL Grip Winter 529 88 04-XX	12	290	121	63
	7	185	103	64
	8	195	109	67
	9	205	115	70
FUNCTIONAL 599 64 98-XX	10	215	121	73
	12	230	133	79
FUNCTIONAL Winter 599 64 97-XX	7	235	108	87
	8	245	114	90
	10	260	126	96
	12	272	132	81
TECHNICAL 599 65 03-XX	9	235	108	87
	10	245	114	90
	12	260	126	96
	9	225	102	82
TECHNICAL Light 599 65 11-XX	8	225	102	82
	9	235	108	85
	10	245	114	88
	12	260	126	94
TECHNICAL Grip 529 88 03-XX	7	230	90	57
	8	240	95	60
	9	250	100	64
	10	260	105	67
TECHNICAL Grip 529 88 03-XX	12	280	112	72



		A	B	C	
size		length	width	thumb	
			left*	right	
FUNCTIONAL chain saw protection 0 16m/s 599 65 16-XX	7	180	103	99	64
	8	190	109	105	67
	9	200	115	111	70
	10	210	121	117	73
	12	225	133	129	79
TECHNICAL chain saw protection 1 20 m/s 599 65 12-XX	7	220	102	98	81
	8	230	108	104	84
	9	240	115	111	87
	10	250	120	117	90
	12	265	130	125	96

* with protection material